

NITREX



- Nitrex/PVC through-the-weave rubber covered construction
- Good resistance to abrasion in standard rib
- Excellent resistance to abrasion in HD rib
- High resistance to oil, gasoline, and a wide range of chemicals
- Very resistant to both contact and radiant heat
- Lightweight hose, remaining flexible even at low temperatures
- Diameters: 1", 1 1/2", 1 1/2" HD, 1 3/4", 1 3/4" HD, 2", 2" HD, 2 1/2", 2 1/2" HD, 3", 4", 5", 6"
- Easy to handle and coil
- High burst strength
- No maintenance or drying required
- Designed for 10 years of service life
- 10 Year warranty
- Colors: red & yellow (other colors available upon request)
- Lifetime Warranty against tube delamination



HD version

INSIDE DIAMETER	THICKNESS	WEIGHT/ FT. UNCOUPLED	WORKING PRESSURE	TEST PRESSURE	BURST PRESSURE
1"	1 1/4"	.18 lbs.	300 psi	600 psi	900 psi
*1 1/2"	1 3/4"	.26 lbs.	300 psi	600 psi	900 psi
*1 1/2" HD	1 13/16"	.33 lbs.	300 psi	600 psi	900 psi
*1 3/4"	1 15/16"	.31 lbs.	300 psi	600 psi	900 psi
*1 3/4" HD	2 1/16"	.38 lbs.	300 psi	600 psi	900 psi
2"	2 1/4"	.34 lbs.	300 psi	600 psi	900 psi
2" HD	2 5/16"	.44 lbs.	300 psi	600 psi	900 psi
*2 1/2"	2 3/4"	.45 lbs.	250 psi	500 psi	750 psi
*2 1/2" HD	2 7/8"	.56 lbs.	300 psi	600 psi	900 psi
*3"	3 1/4"	.58 lbs.	250 psi	500 psi	750 psi
*4"	4 5/16"	.79 lbs.	250 psi	500 psi	750 psi
*5"	5 5/16"	1.05 lbs.	225 psi	450 psi	675 psi
6"	6 5/16"	1.40 lbs.	225 psi	450 psi	675 psi

* UL LISTED